# Mobile refuel tanks directly from the loading area



Mobile tanks for Diesel and AdBlue (AUS 32, UREA) No ADR (in line with "craftsmanship regulation")

Quick, handy refueling, straight from loading space.

#### **Basic Equipment / Features:**

- Large storage space, further equipment can be mounted
- Lid with gas spring, lockable, with 4 keys
- Extremely robust (wallthickness up to 11,5 mm)
- ► Selfpriming pump 12 V (24 V on option)
- Automatic nozzle with nozzle holder (manual nozzle with AdBlue tank)
- ▶ 6 m filling hose
- ▶ 4 m battery cable with clamp
- ► Large 4"filling port and vent
- ▶ Comes with 2 steel shackles to fix the tank on front side
- ► Integrated fork lift spaces

Very wide range of applications – extremely robust and UV resistant mobile Tank

#### **AdBlue Version**

- Membrane pump 12 V
- Manual nozzle
- ▶ 6 m filling hose for AdBlue



Mobile Tank for AdBlue 4001



Mobile Tank Diesel 2001



Lid with gas spring



large 4" filling port



Mobile Tank Diesel 400l

particularly robust tank wall




large tank interior

## **Mobile refuel Tanks**



## **Optional accessories:**







level indicator



digital flow meter K24

### **Technical details**

Fortis Tank	200 liter		400 liter	
	Diesel*	AdBlue	Diesel*	AdBlue
Flow rate max.	50 l/min	36 l/min	50 l/min	36 l/min
Dimensions ca.	108 x 80 x 58 mm		108 x 80 x 83 mm	
Empty Weight - Tank only	43 kg		53 kg	
wall thickness	between 7,2 and 10 mm		between 7,9 and 11,5 mm	
filling plug	4"		4"	
level indicator (on optional)	120828FÜLL	×	120828FÜLL	×
Flow meter digital K24 (on option)	131839	1318170 + P15776	131839	1318170 + P15776
Art.No.	120828FB200D	120828FB200A	120828FB400D	120828FB400A

The transport of urea does not require permits.

All data, descriptions, photos, images and dimensions of the entire brochure are non binding and shall be used for visualisation only. We reserve the right for amendments and can not be held liable for printing errors.



**ZUWA-Zumpe GmbH** 

Franz-Fuchs-Str. 13-17 D-83410 Laufen www.zuwa.de Phone: +49 8682 8934-50 Fax.: +49 8682 8934-850

E-Mail: export@zuwa.de

<sup>\*</sup>In exemption from ADR sections 1.1.3.1.a) and 1.1.3.1.c)