# Company

PVR continues the production of vacuum pumps which began in the Sixties, with the aid of new technologies, as requested from the market. The experience built in over 50 years, the development of new products, the modern production lines and a trained staff allow us to







www.pvr.it





# POR PORT OF THE PO

# Service

PVR guarantees a qualified advice for every inquiry thanks to its skilled technical/sales office that supports every project.

The Service Department assists and advises our customers with scheduled servicing qualified overhauls and spare parts promptly delivered.





## PVR Srl

### **HEADQUARTERS:**

Via Santa Vecchia, 107 - 23868 Valmadrera (LC), Italy T +39 0341 1918 51 - F +39 0341 1918 599 sales@pvr.it - www.pvr.it

### **LOCAL UNIT:**

Via IV Novembre, 104F 23868 Valmadrera (LC), Italy



12102-FN

# M Series

# **Diaphragm vacuum pumps and compressors**

Diaphragm pumps of "M41 and M71 Series" are completely oil free. They can be used either to create vacuum or pressure. The "M41 Series" has a Ryton ®-made pump body, the diaphragm and the gasket VITON, EPDM or PTFE.

The "M71 Series" has the pump body made of galvanized anticorodal aluminium, the diaphragms and the gaskets can be made of EPDM or VITON. All the pumps are available either with single or double-head to be used either in parallel or in series.

The "M41 Series" can also be supplied with three or four heads to increase the capacity.

# **Applications**


Packaging machines with modified atmosphere Blister packaging machines Bottle fillings Chemical processes Degassing materials Solvent recovery systems Distillation systems

Dental equipments Cosmetic industries Laboratories Ozone generators Gas analysers









M41S ACO4 HT	M71S AC05

		M41S	M41S	M41BX		M41BX		<b>EMMEBOX</b>	M41S	M71S	M71S	M71BX		M71BX			
		AC04	DC52	AC04		DC53		AC04	AC04 HT	AC05	DC54	AC08		DC55			
Nominal pumping speed	d I/min	EO LI-	50 Hz	8		Parallel	16	6 Parallel	17			30		Parallel	56	Parallel	62
		30 HZ	٥	8,5	Series	8	Parallel	1/	9.5	7	30	33	Series	30	Parallel	02	
		60 Hz	9.5		Parallel	19	Series	8.5	/	36	33	Parallel	68	Series	33		
					Series	9.5	Series	0.0			30		Series	36	Jenes	33	
Ultimate pressure (abs)	mbar		200	200	Parallel	200	Parallel	200	200	180	100	100	Parallel	100	Parallel	100	
					Series	40	Series	40					Series	15	Series	15	
Pressure (gauge)	bar	bar	2	2.5	2		3		2	2	0.7	0.7	Parallel	0.7	Parallel	0.7	
													Series	1.3	Series	1.3	
Voltage*	V		110/230 AC	12/24 DC		110/230 12/24 AC DC			110/230 AC	230 AC	110/230 AC	12/24 DC	110/230 AC		12/24 DC		
Overall dimensions	mm		140×74 ×104	131x60 x104	147x1 x10		149x133 x75		180x120 x116	150x74 x142	169x81 x130	177x90 x130	194x153 x94		230x153 x94		
Total weight	kg		1.31	0.62	1.59	9	1.19	9	2.8	1.85	2.13	1.90	3.20	0	2.70	)	

<sup>\*</sup> Motors having different voltages could be supplied on demand





Special series HT with body and valve made of AISI 316. Hot head.Max. temperature of the pumped medium up to 200°C.

# Designed to offer the customer numerous benefits

- Dry diaphragm technology
- · Compact and low weight
- Versatile for various applications with the possibility to choose diaphragms of different materials
- Reduced maintenance









